

MODEL #

RFUB

TECHNICAL SPECIFICATION




MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:					ACCESSORIES:				
PROJECT:					NOTES:				
TYPE:					AREA:				

FEATURES

PRODUCT IMAGE

APPLICATION
Ceiling
Indoor

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT
---------------------	---------------------	------------------	---------------------	-------------------

LED CHIPS USED LG/NICHIA/SAMSUNG	TESTED LM80 AND LM82	CRI 80+	LIFE HOURS 50,000
-------------------------------------	----------------------------	------------	----------------------

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



ASL LIGHTING

725 East state St. Trenton,NJ 08609 | info@asllightng.com | www.asllighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609
Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.
© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
White Acrylic

STANDARD FINISH
Satin Nickel

MODEL #RFUB ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE	 27K	D10 - D10 3/8 H2 5/8
W12 - 12		 30K	D15 - D15 H2 5/8
W15 - 15	DV - 120V/277V NON DIMMABLE	 35K	D19 - D19 H2 5/8
W20 - 20	TD - 120V TRIAC/ELV DIMMABLE	 40K	
W24 - 24	DVD - 120/277V 0-10V DIMMABLE	 50K	
W31 - 31			

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) CCS - Cable Cord Suspension System FI - Finial PK1 - Canopy/Pendant Kit/1 ROD PK2 - Canopy/Pendant Kit/2 RODS PK3 - Canopy/Pendant Kit/3 RODS

CUSTOM FINISH OPTIONS

 FGB Gloss Black	 FGBR Gloss Brass	 FGBZ Gloss Bronze	 FGW Gloss White	 FMB Matte Black
 FMBR Matte Brass	 FMW Matte White	 ORB Oil Rubbed Bronze		

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request