

MODEL #

TLM3

TECHNICAL SPECIFICATION



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION
Indoor
Sconce/Mini Pendant LED Lamp

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

4000K
COOL WHITE

5000K
DAYLIGHT

TESTED LM80 AND LM82	CRI 80+	LIFE HOURS 50,000
--------------------------------	-------------------	-----------------------------

LED GU24 BULB OR MEDIUM BULB

LED BULB WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
6	600	450
9	900	675
12	1200	900

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Opal Glass

STANDARD FINISH
Satin Nickel

MODEL #TLM3 ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W6 - 6	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE	 27K	W12 - W12 H9 3/8 D4 3/4
W9 - 9		 30K	W18 - W18 H9 3/8 D4 3/4
W12 - 12	ND - 120V NON DIMMABLE	 40K	W24 - W24 H9 3/8 D4 3/4
	DV - 120V/277V NON DIMMABLE	 50K	W4 - W4 3/8 H9 3/8 D4 3/4

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control
CUSTOM FINISH OPTIONS

Not seeing what you're looking for? Contact us to discuss more options.

