

MODEL #

TLM4

TECHNICAL SPECIFICATION



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

 **APPLICATION**
Indoor
Sconce/Mini Pendant LED Lamp

 **LOCATION**
Damp



LIGHT PROPERTIES

Available Kelvin Options:

 2700K
WARM WHITE

 3000K
SOFT WHITE

 4000K
COOL WHITE

 5000K
DAYLIGHT

TESTED
LM80 AND LM82

CRI
80+

LIFE HOURS
50,000

LED GU24 BULB OR MEDIUM BULB

LED BULB WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
6	600	450
9	900	675
12	1200	900

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Opal Glass

STANDARD FINISH
Satin Nickel

MODEL #TLM4 ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W6 - 6 W9 - 9 W12 - 12	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE	 27K  30K  40K  50K	W12 - W12 H9 3/8 D4 3/4 W18 - W18 H9 3/8 D4 3/4 W24 - W24 H9 3/8 D4 3/4 W4 - W4 3/8 H9 3/8 D4 3/4

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control
CUSTOM FINISH OPTIONS

Not seeing what you're looking for? Contact us to discuss more options.

