



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION

Indoor
Sconce

LOCATION

Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

4000K
COOL WHITE

5000K
DAYLIGHT

TESTED
LM80 AND LM82

CRI
80+

LIFE HOURS
50,000

LED GU24 BULB OR MEDIUM BULB

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
6	600	450

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Opal Glass

STANDARD FINISH
Oil Rubbed Bronze

MODEL #TLO ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W6 - 6	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE	 27K  30K  40K  50K	W4 - W4 7/8 H9 5/8 D6 1/4

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control
CUSTOM FINISH OPTIONS
 FGB Gloss Black  FGBR Gloss Brass  FGBZ Gloss Bronze  FGW Gloss White  FMB Matte Black  FMBR Matte Brass  FMW Matte White  ORB Oil Rubbed Bronze

Not seeing what you're looking for? Contact us to discuss more options.

