

MODEL #

TLO2

TECHNICAL SPECIFICATION



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

 **APPLICATION**
Indoor
Sconce/Mini Pendant LED Lamp

 **LOCATION**
Damp



LIGHT PROPERTIES

Available Kelvin Options:

 2700K WARM WHITE	 3000K SOFT WHITE	 4000K COOL WHITE	 5000K DAYLIGHT
--	---	---	---

TESTED LM80 AND LM82	CRI 80+	LIFE HOURS 50,000
-------------------------	------------	----------------------

LED GU24 BULB OR MEDIUM BULB

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	900	675

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Opal Glass

STANDARD FINISH
Oil Rubbed Bronze

MODEL #TLO2 ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE	27K 30K 40K 50K	W13 - W13 1/4 H9 5/8 D6 1/4

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control
CUSTOM FINISH OPTIONS

Not seeing what you're looking for? Contact us to discuss more options.

