

MODEL #

# TSL-BN

TECHNICAL SPECIFICATION



|             |  |          |  |          |  |              |  |       |  |
|-------------|--|----------|--|----------|--|--------------|--|-------|--|
| MODEL #:    |  | WATTAGE: |  | VOLTAGE: |  | KELVIN:      |  | SIZE: |  |
| TECHNOLOGY: |  |          |  |          |  | ACCESSORIES: |  |       |  |
| PROJECT:    |  |          |  |          |  | NOTES:       |  |       |  |
| TYPE:       |  |          |  |          |  | AREA:        |  |       |  |

FEATURES

PRODUCT IMAGE

- APPLICATION
- Indoor
- Outdoor
- Sconce
- LOCATION
- Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K WARM WHITE

3000K SOFT WHITE

3500K NEUTRAL

4000K COOL WHITE

5000K DAYLIGHT

|                   |               |     |            |
|-------------------|---------------|-----|------------|
| LED CHIPS USED    | TESTED        | CRI | LIFE HOURS |
| LG/NICHIA/SAMSUNG | LM80 AND LM82 | 80+ | 50,000     |

| WATTAGE | SOURCE LUMENS @40K | DELIVERED LUMENS |
|---------|--------------------|------------------|
| 9       | 1259               | 1007             |
| 12      | 1520               | 1216             |
| 15      | 1750               | 1400             |
| 20      | 2494               | 1995             |
| 24      | 2793               | 2234             |
| 31      | 4000               | 3200             |

| VOLTAGE                             |
|-------------------------------------|
| Standard:<br>ND - 120V NON DIMMABLE |
| DV - 120V/277V NON DIMMABLE         |
| TD - 120V TRIAC/ELV DIMMABLE        |
| DVD - 120/277V 0-10V DIMMABLE       |



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION  
Polycarbonate

STANDARD LENS  
Smooth White Polycarbonate

STANDARD FINISH  
Brushed Nickel

MODEL #TSL-BN ORDER FORM

| WATTAGE * | VOLTAGE                                                                                                                                         | KELVIN                                                                                | SIZE                   |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|------------------------|
| W9 - 9    | Standard Voltage:<br>ND - 120V NON DIMMABLE<br><br>DV - 120V/277V NON DIMMABLE<br>TD - 120V TRIAC/ELV DIMMABLE<br>DVD - 120/277V 0-10V DIMMABLE |  27K | W5 - W5 1/4 H11 D2 3/4 |
| W12 - 12  |                                                                                                                                                 |  30K |                        |
| W15 - 15  |                                                                                                                                                 |  35K |                        |
| W20 - 20  |                                                                                                                                                 |  40K |                        |
| W24 - 24  |                                                                                                                                                 |  50K |                        |
| W31 - 31  |                                                                                                                                                 |                                                                                       |                        |

\* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY                                                                                                                        | ACCESSORIES                                                                              |
|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| EMG - Emergency<br>EMGR - Emergency Remote<br>OS - Occupancy Sensor<br>OSCD - Occupancy Sensor Step Dimming<br>PC - Photo Control | BB - Back Box (Extended Base)<br>BBX - Back Box (Extended Base) (Conduit Holes Optional) |

Not seeing what you're looking for? Contact us to discuss more options.

