

MODEL #

# UFO3

TECHNICAL SPECIFICATION



|             |  |          |  |          |  |              |  |       |  |
|-------------|--|----------|--|----------|--|--------------|--|-------|--|
| MODEL #:    |  | WATTAGE: |  | VOLTAGE: |  | KELVIN:      |  | SIZE: |  |
| TECHNOLOGY: |  |          |  |          |  | ACCESSORIES: |  |       |  |
| PROJECT:    |  |          |  |          |  | NOTES:       |  |       |  |
| TYPE:       |  |          |  |          |  | AREA:        |  |       |  |

FEATURES

PRODUCT IMAGE

 **APPLICATION**  
Ceiling  
Outdoor

 **LOCATION**  
Wet



LIGHT PROPERTIES

Available Kelvin Options:



|                   |               |     |            |
|-------------------|---------------|-----|------------|
| LED CHIPS USED    | TESTED        | CRI | LIFE HOURS |
| LG/NICHIA/SAMSUNG | LM80 AND LM82 | 80+ | 50,000     |

| WATTAGE | DELIVERED LUMENS |
|---------|------------------|
| 100     | 13000            |
| 150     | 19500            |

| VOLTAGE                     |
|-----------------------------|
| Standard:                   |
| DV - 120V/277V NON DIMMABLE |



ASL LIGHTING

725 East state St. Trenton,NJ 08609 | info@aslightng.com | www.aslighting.com  
TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609  
Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.  
© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

Die Cast Aluminum

STANDARD LENS

Polycarbonate

STANDARD FINISH

Black

MODEL #UFO3 ORDER FORM

| WATTAGE *  | VOLTAGE                                              | KELVIN                                                                                | SIZE               |
|------------|------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------|
|            |                                                      |                                                                                       |                    |
| W100 - 100 | Standard Voltage:<br><br>DV - 120V/277V NON DIMMABLE |  50K | D14.1 - D14.1 H7.9 |
| W150 - 150 |                                                      |                                                                                       | D17.0 - D17.0 H8.3 |

*\* Up to 200W available on fixtures over 24".*

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY                                                                       |
|----------------------------------------------------------------------------------|
|                                                                                  |
| EMG - Emergency<br>OS - Occupancy Sensor<br>OSCD - Occupancy Sensor Step Dimming |

*Not seeing what you're looking for? Contact us to discuss more options.*



ASL LIGHTING

725 East state St. Trenton,NJ 08609 | info@asllightng.com | www.asllighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request