







Properties

Cold-rolled Steel	Base Construction
Acrylic	Lens
Vanity	Application
Damp	Location
80	CRI
50,000	Life Hours
Integrated LED	Light Source
Integro	Light Source

Standard Selection

Voltage	120V (non dimming)
Finish	Brushed Nickel
ССТ	3000K
Finish Options	

ССТ	2700K/3000K/3500k/4000K/5000K
CCT Options	
ORB	White
Brushed Nickel	Gold/Brass
Black	Bronze
Finish Options	
ССТ	3000K

_			
()	ntı	ior	19

Size	Dimensions	Wattage	Voltage	Lumens
VASE-22	L:22.5" H:2" E:2.3"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
VASE-34	L:34" H:2" E:2.3"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
VASE-46	L:46" H:2" E:2.3"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200

Not seeing what you're looking for?

Contact us!

info@asllighting.com