



Properties

Base Construction	Steel
Lens	Glass
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	ORB
CCT	4000K

Finish Options

 Black	 Bronze
 Brushed Nickel	 Gold/Brass
 ORB	 White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBDSA-31	H:31" W:4.8" E:4.2"	25/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/3900/5200
VBDSA-12	H:12" W:4.8" E:4.2"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
VBDSA-24	H:24" W:4.8" E:4.2"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

Options

- BBX-Backbox W/ 3/4" Conduit hole
- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com