




MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION
Indoor
Sconce

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Frosted Acrylic

STANDARD FINISH
Nickel

MODEL #WFG ORDER FORM

WATTAGE	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K	D11 - D11 H2.4 Lumens 1050
W12 - 12		 30K	D14 - D14 H2.4 Lumens 1600
W15 - 15		 35K	
W20 - 20		 40K	
W24 - 24		 50K	
W31 - 31			

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control
CUSTOM FINISH OPTIONS
 FGB Gloss Black  FGBR Gloss Brass  FGBZ Gloss Bronze  FGW Gloss White  FMB Matte Black  FMBR Matte Brass  FMW Matte White  ORB Oil Rubbed Bronze

Not seeing what you're looking for? Contact us to discuss more options.

